

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION AND COMPANY INFORMATION

PRODUCT NAME: MULTISPEC **DATE PRINTED:** 4/15/2008
PRODUCT NUMBER:
PRODUCT USE/CLASS: Waterborne Multicolor
COLOR SERIES: 996000 - 996999, 998000 - 998999

SUPPLIER:

NEW FINISH PRO
8375 CAMINO SANTA FE, SUITE A
SAN DIEGO, CA 92121
PHONE: 800-NEW-FINISH (800) 639-3464
FAX: 858-554-0555

CHEMTREK 24-HOUR EMERGENCY TELEPHONE: 800-424-9300

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT LESS THAN	%
1	Diethylene Glycol Monoethyl Ether	111-77-3	2.20%	
2	Ethylene Glycol n-Butyl Ether	111-76-2	1.10%	

EXPOSURE LIMITS

ITEM

- 5 ppm TWA8 ACGIH, 25 ppm TWA8 OSHA.
- 25ppm TWA8 (skin) ACGIH & OSHA.

Additional non-hazardous chemicals listed to comply with New Jersey and Pennsylvania states right-to-know standards: Water 7732-18-5, TSRN 01368, TSRN 01353, Titanium Dioxide 13463-67-7, Silicone Dioxide 112926-00-8.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

EFFECTS OF OVEREXPOSURE - EYE CONTACT: With liquid contact, eye irritation can occur. Overexposure to vapors could result in eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:

EFFECTS OF OVEREXPOSURE - INHALATION: Overexposure to vapors could result in upper respiratory tract irritation. Prolonged breathing of vapors may cause nausea, headache, weakness, and/or dizziness.

SECTION 3 - HAZARDS IDENTIFICATION (Continued)

EFFECTS OF OVEREXPOSURE - INGESTION: Ingestion of this product may cause nausea, vomiting, and/or diarrhea.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No known long-term or chronic effects.

PRIMARY ROUTE(S) OF ENTRY: Ingestion, inhalation, and skin.

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush immediately with large amounts of water for at least 15 minutes. Take to physician for medical treatment.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin thoroughly with soap and water.

FIRST AID - INHALATION: If overcome by exposure, remove victim to fresh air.

FIRST AID - INGESTION: Induce vomiting. Get immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: N/A, Non-flammable.
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: None.
UPPER EXPLOSIVE LIMIT: None.

EXTINGUISHING MEDIA: Use all-purpose ABC extinguisher or appropriate extinguisher for the type of material burning. Liquid material should not support fire.

USUAL FIRE AND EXPLOSION HAZARDS: During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIREFIGHTING PROCEDURES: Not applicable.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Confine in small area. Clean up with approved absorbent materials. May use water to flush area or clean. Place in closed container for disposal.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Close container after each use. **KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.**

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION: Do not breathe vapors or spray mist. Use with adequate ventilation. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. Wear respiratory protection, vapor/dust respirator (NIOSH/MSHA approved respirator).

SKIN PROTECTION: Avoid contact with skin, wear gloves.

EYE PROTECTION: Avoid contact with eyes, wear safety glasses.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: 210 - 396 Deg. F

APPEARANCE: Multicolor paint particles.

SOLUBILITY IN H2O: Yes

FREEZE POINT: 32 Deg. F

WEIGHT PER GALLON: 9.06 lb/gal.

VAPOR DENSITY: Heavier than air.

EVAPORATION RATE: Slower than
Butyl Acetate.

SPECIFIC GRAVITY:

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Avoid strong acids and water-reactive materials. Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Incineration will produce smoke, carbon monoxide, carbon dioxide, and oxides of nitrogen.

STABILITY: Stable.

SECTION 11 - TOXICOLOGICAL INFORMATION/PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ENVIRONMENTAL HAZARDS

None known.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION INFORMATION

Not regulated under DOT as a hazardous material. Not hazardous, non-combustible.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: This product is not regulated as a potential carcinogen by the OSHA Hazard Communication Standard.

TSCA: All ingredients have been listed with TSCA.

CERCLA - SARA HAZARD CATEGORY:

FIRE HAZARD

SARA TITLE III, SECTION 311/312: Immediate (acute).

SARA TITLE III, SECTION 313: This product contains the following toxic chemicals that are subject to the reporting requirements of the EPCRA Section 313: Certain Glycol Ethers 3.3% wt.

CALIFORNIA PROPOSITION 65: This product contains chemicals suspected or known to the State of California to cause birth defects or other reproductive harm. This product contains trace levels (<40 ppm) of chemicals suspected or known to the State of California to cause cancer.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

DSL/NDL: All ingredients are listed on the Canadian DSL.

CANADIAN WHMIS CLASS: This product is not regulated as a potential carcinogen by the Canadian WHMIS legislation.

SECTION 16 - OTHER INFORMATION

HMIS/NFPA. RATING: HEALTH: 1; FLAMMABILITY: 0; REACTIVITY: 0; PPE, E.

VOLATILE ORGANIC COMPOUNDS (VOCS): Maximum 205 g/l, 1.7 lb/gal, Non-photochemically reactive.

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

SECTION 17 - USER'S RESPONSIBILITY

The responsibility to provide a safe workplace remains with the user. The user should consider the health hazard and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.

The information contained on this MSDS has been checked and, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

(END OF MSDS)
